

TAO-A/V II Series

Bill Acceptor

- Four way bill insertion acceptance.
- Auto-calibrating.
- Secure lockable and removable cashbox with 200, 500 or 1000 note capacity.
- Advanced water resistant design.
- Excellent resistant to humidity environment.
- Support update firmware using a USB flash drive.



ICT

TAO-A/V II Series

Bill Acceptor

TAO-A/V II series is a bill acceptor which features a lockable bill box for high-security with acceptance rate up to 96% or greater.

Specifications



Acceptance Rate

96% or greater



Bill Insertion

Four-way



Bill Width Accepted

62-66 mm/2.44-2.6 inches



Acceptance Speed

Approx. 3 sec. to cash box



Capacity

Approx. 200 notes cashbox
Approx. 500 notes cashbox
Approx. 1000 notes cashbox



Interface

TAO-A IIU: Pulse, 5V ENABLE, NISR,
ICT Protocol, Single Price
TAO-V IIU: Pulse, MDB, ICT Protocol



Power Source

TAO-A IIU: 12V DC(10.8V~13.2V DC)
117V AC(105.3V~128.7V AC)
TAO-V IIU: 12V DC(10.8V~13.2V DC)
24V AC(21.6V~26.4V AC)
34V DC(20V~42.5V DC)



Recommended Applications

Vending, Gaming, Kiosk, Amusement



Power Consumption

TAO-A IIU: 12V DC - Standby: 0.3A, 4W
Operation: 0.9A, 11W
Maximum: 2.6A, 32W
117V AC - Standby: 0.06A, 7W
Operation: 0.12A, 15W
Maximum: 0.4A, 47W
TAO-V IIU: 12V DC - Standby: 0.3A, 4W
Operation: 0.8A, 10W
Maximum: 2.5A, 30W
24V AC - Standby: 0.2A, 5W
Operation: 0.5A, 12W
Maximum: 1.5A, 36W
34V DC - Standby: 0.15A, 6W
Operation: 0.4A, 14W
Maximum: 1.35A, 46W



Dimension

TAO-A/V IIU-P2:
(W)106.3 x (D)174.9 x (H)247.5mm/
(W) 4.19 x (D)6.89 x (H)9.74 inches
TAO-A/V IIU-P5:
(W)106.3 x (D)219.9 x (H)247.5mm/
(W)4.19 x (D)8.66 x (H)9.74 inches
TAO-A/V IIU-P10:
(W)106.3 x (D)318.9 x (H)253.9mm/
(W)4.19 x (D)12.56 x (H)10 inches



Weight

TAO-A/V IIU-P2 : Approx. 1.3 kg/ 2.87 lbs
TAO-A/V IIU-P5 : Approx. 1.5 kg/ 3.31 lbs
TAO-A/V IIU-P10: Approx. 1.72 kg/ 3.79 lbs



Environmental

Operating Temperature: 0°C / 32°F ~55°C / 131°F
Storage Temperature: -30°C / -22°F ~ 70°C / 158°F
Humidity : 30%-85% RH (no condensation)



Built-in USB Port



Advanced water resistant design

Specifications are subject to change without prior notice.



International Currency Technologies

No.28, Ln. 15, Sec. 6, Minquan E. Rd., Neihu Dist., Taipei City 114, Taiwan (R.O.C.)

Phone: +886-2-2793-1236

Fax: +886-2-2793-6125

Email: sales@ictgroup.com.tw (Product Information)

fae@ictgroup.com.tw (Technical Service)

Website: www.ictgroup.com.tw